

远程文件

Subtitle

2022/10/05




Table of Contents

远程文件	1
做成模块	1
参考	3

远程文件

puppet 4.4 之前的版本不支持http方式同步文件

snippet.puppet

```
define remote_file($remote_location=undef, $mode='0644', $service=undef, $md5=undef){  
    exec{ "retrieve_${title}":  
        unless => "/usr/bin/md5sum ${title} |/usr/bin/grep -w ${md5}",  
        command => "/usr/bin/curl -s ${remote_location} --create-dirs -o /tmp${title} &&  
        /usr/bin/md5sum /tmp${title} |/usr/bin/grep -w ${md5} && /usr/bin/mv -f ${title} /tmp &&  
        /usr/bin/mv -f /tmp${title} ${title} || exit 1",  
        #creates => $title,  
    }  
  
    file{$title:  
        mode  => $mode,  
        require => Exec["retrieve_${title}"],  
        notify => Service["$service"]  
    }  
}
```



creates => \$title, 此参数是文件不存在时才创建，应删去

调用示例

snippet.puppet

```
remote_file {  
    '/usr/local/bin/kube-proxy':  
        mode => '0755',  
        service => 'kube-proxy',  
        md5 => '7f88a9057292971b10ad6de794f9ba62',  
        remote_location => 'http://yum.intra.xxx.cn/soft/k8s/kube-proxy'  
}
```

做成模块

snippet.bash

```
[root@itop puppet]# tree utils/  
utils/
```

```
└── manifests
    ├── init.pp
    └── wget.pp
```

init.pp

[snippet.puppet](#)

```
class utils {
    include utils::wget
}
```

wget.pp

[snippet.puppet](#)

```
class utils::wget {
    define remote_file($remote_location=undef, $mode='0644', $service=undef, $md5=undef){
        exec{ "retrieve_${title}":
            unless => "/usr/bin/md5sum ${title} |/usr/bin/grep -w ${md5}",
            command => "/usr/bin/curl -s ${remote_location} --create-dirs -o /tmp${title} &&
            /usr/bin/md5sum /tmp${title} |/usr/bin/grep -w ${md5} && /usr/bin/mv -f ${title} /tmp &&
            /usr/bin/mv -f /tmp${title} ${title} || exit 1",
            #creates => $title,
        }
        file{$title:
            mode  => $mode,
            require => Exec["retrieve_${title}"],
            notify => Service["$service"]
        }
    }
}
```

调用

[snippet.puppet](#)

```
class k8sdev::worker {
    include utils::wget
    utils::wget::remote_file {
        '/usr/local/bin/kube-proxy':
            mode => '0755',
            service => 'kube-proxy',
            md5 => '7f88a9057292971b10ad6de794f9ba62',
            remote_location => 'http://yum.intra.xxx.cn/soft/k8s/kube-proxy'
    }
}
```

参考

- <https://serverfault.com/questions/639966/can-puppet-file-source-be-from-a-web-service>
- <https://stackoverflow.com/questions/18844199/how-to-fetch-a-remote-file-e-g-from-github-in-a-puppet-file-resou>

Printed on: 2022/10/05 18:20

Convert to img Failed!